



1375055-1

SL110 Series Modular Jack, RJ45, category 6, T568A/T568B, unshielded, without dust cover, light almond

Product Classification

Portfolio	NETCONNECT®
Product Series	SL Series
Product Type	Modular jack
Regional Availability	Asia Latin America North America

Body Features

110 Block Material	Polycarbonate
Inverted Jack Face	Yes

Configuration Features

Keyed	No
Number of Positions	8
Wiring Pattern	Universal

Contact Features

Contact Base Material	Beryllium copper
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.00 µin 1.27 µm

Dimensions

Insulated Conductor Outside Diameter	0.057 in 1.45 mm
Solid Wire Range	.51 mm ² .65 mm ²
Stranded Wire Range	.14 mm ² .2 mm ²
Wire Range	22 AWG 24 AWG 26 AWG

Housing Features

Housing Color	Light almond
Housing Material	Polycarbonate

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

1375055-1

Mechanical Attachment

Mounting Type SL Series Faceplate

Other

Comment With strain relief.

Packaging Features

Packaging Method Poly Bag

Packaging Quantity 1

Product Type Features

Performance Category Category 6

Shielded No

Applies To Panel

Cable Type Unshielded Twisted Pair

Connector Type Connector Assembly

Dust Cover Without

Jack Type RJ45

Termination Features

Termination Method to Wire/Cable Insulation Displacement Crimp (IDC)

Termination Style SL Termination Tool

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant